

RATINGS/PERFORMANCE	
	HTR-B151 SDI Input Card (3G-SDI version also available)
HD-SDI Input	4 ch BNC 4 inputs (2ch input for 3G-SDI)
Input Signal	SMPTE 292M / SMPTE 424M Embedded Audio Supported
	1080p/50, 59.94, 1080i/50,59.94, 1080p/23.98, 1080p/23.98sF, 720p/50, 59.94
Cable length	100 m (HD-SDI), 50 m (3G-SDI) with 5C-FB
External dimensions	142 mm (W) x 21 mm (H) x 108 mm (D) excl. protrusions
Weight	Approx. 0.2 kg
	HTR-B152 SDI Input Card (3G-SDI version also available)
HD-SDI Input	4 ch 6 BNC outputs (2x OUT1 & 2x OUT2), 2ch output for 3G-SDI
Input Signal	SMPTE 292M / SMPTE 424M Embedded Audio Supported
	1080 p/50, 59.94, 1080 i/50,59.94, 1080 p/23.98, 1080 p/23.98sF, 720 p/50, 59.94
Cable length	100 m (HD-SDI), 50 m (3G-SDI) with 5C-FB
External dimensions	142 mm (W) x 21 mm (H) x 108 mm (D) excl. protrusions
Weight	Approx. 0.2 kg
	HTR-B153 HD-SDI 2 IN/2 OUT Card (3G-SDI version also available)
HD-SDI Input	2ch Input + 2ch Output 4 BNC
Input Signal	SMPTE 292M / SMPTE 424M Embedded Audio Supported
	1080 p/50, 59.94, 1080 i/50,59.94, 1080p/23.98, 1080p/23.98sF, 720p/50, 59.94
Cable length	100 m (HD-SDI), 50 m (3G-SDI) with 5C-FB
External dimensions	142 mm (W) x 21 mm (H) x 108 mm (D) excl. protrusions
Weight	Approx. 0.2 kg